SOILS

ВY

A. W. SKEMPTON AND A. W. BISHOP IMPERIAL COLLEGE, LONDON

Chapter X of Building Materials their Elasticity and Inelasticity Edited by M. Reiner with the assistance of A. G. Ward



1954 NORTH-HOLLAND PUBLISHING COMPANY AMSTERDAM SOILS

ВY

A. W. SKEMPTON and A. W. BISHOP IMPERIAL COLLEGE, LONDON

Chapter X of Building Materials their Elasticity and Inelasticity Edited by M. Reiner with the assistance of A. G. Ward



1954 NORTH-HOLLAND PUBLISHING COMPANY AMSTERDAM

CHAPTER X

SOILS

ВY

A. W. SKEMPTON AND A. W. BISHOP

IMPERIAL COLLEGE, LONDON

CONTENTS: 0. Introduction, 418. - 1. The nature and description of soils, 419. -1.1. Density, water content, etc., 419. - 1.2. Mineralogy and particle size, 420. - 1.3. The Atterberg limits, 421. - 1.4. Activity of clays, 424. -2. Permeability, 425. - 3. The principle of effective stress, 427. - 4. Consolidation, 431. - 4.1, Physics of consolidation, 431. - 4.2. The oedometer test and one-dimensional consolidation, 433. - 4.3. Triaxial consolidation, 438. - 5. Shear strength and stress-strain-time relationships, 441. -5.1. Definition of shear strength, 441. - 5.2. Apparatus for the measurement of shear strength, 441. - 5.3. Stress-strain curves, 446. - 5.4. Rate of deformation, 449. - 6. Practical criteria of failure, 452. - 6.0. Introduction, 452. - 6.1. Undrained strength of saturated soils, 453. - 6.2. Undrained strength of anisotropically consolidated saturated clays, 460. - 6.3. Undrained strength of partially saturated soils, 462. - 6.4. Drained shear strength, 463. - Basic shear strength properties, 467. - 7.1. Influence of rate of volume change at failure, 467. - 7.2. Failure criterion, 470. -7.3. Relationship between strength and water content, 473. - 7.4. Relationship between ϕ' and ϕ_d , 474. - 8. Sensitivity and thixotropy of clays, 475. -8.1. Sensitivity, 475. - 8.2. Leaching of marine clays, 475. - 8.3. Thixotropy, 477.

SPECIAL SYMBOLS AND TERMINOLOGY

The notation used in this Chapter is the one agreed upon for the international journal of soil mechanics "Geotechnique".

Wherever the symbol used here has a different meaning in the rest of the book the explanation has been marked with a star *.

 a_{r} = effective contact area

 C_{ϵ} = compressibility of soil structure

 C_u = compressibility of pore water

 c_u = apparent cohesion of undrained specimen

 c_v = coefficient of consolidation

 $D_{10} = \text{ten } 0/0 \text{ size of particles (see § 1)}$

e = void ratio *